



Alpha is not just a customised product with an innovative design, but also a working tool for the lighting designers and engineers. It combines the aesthetic with the latest LED technological standards and meets the various needs of the customers in a bespoke way: it allows them to "think big" offering totally unexpected results even to large scale projects

TECHNICAL FEATURES

Aluminium body, painted electrostatically in selected colour.
High efficient polycarbonate satin cover.
Direct & Indirect Illumination (Pure light without IR/UV radiation)
Operation Life of 50,000 hours with efficiency > 80% of the initial luminous flux.
CRI min. 80
SDCM 3

DIMENSIONS

Diameter: 610mm, 805mm, 1090mm or 1470mm
Depth: 25mm
Height: 1000mm, 2000mm, 3000mm or 4000mm

ORDER CODES

ORDER CODE	DIAMETER	LUMINOUS EFFICIENCY	OUTPUT	POWER	COLOUR TEMPERATURE
EUAA/610/3K/IN	610 mm	133 Lm/W	3990 LM	30 W	3000K
EUAA/610/4K/IN	610 mm	140 Lm/W	4200 LM	30 W	4000K
EUAA/805/3K/IN	805 mm	133 Lm/W	5320 LM	40 W	3000K
EUAA/805/4K/IN	805 mm	140 Lm/W	5600 LM	40 W	4000K
EUAA/1090/3K/IN	1090 mm	133 Lm/W	7315 LM	55 W	3000K
EUAA/1090/4K/IN	1090 mm	140 Lm/W	7700 LM	55 W	4000K
EUAA/1470/3K/IN	1470 mm	133 Lm/W	9310 LM	70 W	3000K
EUAA/1470/4K/IN	1470 mm	140 Lm/W	9800 LM	70 W	4000K

OPTIONS

DALI Dimmable: /DA
White Finish: /WH
Black Finish: /BK
Grey Finish: /GR
Specific RAL Colour: /RAL****